

## UPRIGHTS

Choice of the following materials:

1. Aluminium - 75mm x 75mm (3.5mm wall thickness). Powder-coated.  
Grade: 6082-T6, anodised 15um.  
Fixture Method: Drill + threaded inserts fitted, mild steel (zinc).
2. Galvanised Steel - 75mm x 75mm internally coated (2.5mm wall thickness). Powder-coated.  
Grade: C450L0  
Fixture Method: Drill + threaded inserts fitted, mild steel (zinc).  
Strength meets the strength requirements of Section 2.2.2 of AS 4685.1-2004

Caps: Moulded plastic (polyethylene).

## POWDER COATING

All steel components have a lead and TGIC free, baked polyester powder-coat finish.

Our finish of 80-120 microns greatly exceeds the required Australian Standard (AS3715-2002) of 60 microns.

## PLATFORMS AND PLATFORM INFILLS

Fully reinforced, Marine Grade Aluminium (5005-H34). Minimum thickness 3mm.

Finish: Textured powder-coat.

## STEEL PLAY COMPONENTS

1. Galvanised Steel - Galtube plus, meeting the specifications C350L0.
2. Stainless Steel – 304 and 316 Grade Stainless Steel.

Finish: Powder-coated.

## PLASTIC PLAY COMPONENTS

- Rota-moulded - Polyethylene (UV stabilised, rating 8) with 930 density.
- Injection Moulded – 30% Glass Filled Nylon.

## CHAINS

1. 6mm short link stainless steel chain.
2. 6mm and 8mm short link zinc passivated or galvanised chains.

## STANDARDS

Complies with relevant Australian Standards including: AS 4685:2014 (P1-6) | AS 4685.0:2017 | AS/NZS 4422:2016

\*All information is commercial in confidence and is the property of Forpark Australia. All information is correct as at February 2019. For details regarding Australian standards, warranties, insurances, QA and installation, please contact your local office

## PANELS

Available in the following materials:

1. Galvanised steel with powder-coated finish.
2. Rota-moulded polyethylene (UV stabilised, rating 8) with 930 density.
3. Tri-laminate high density polyethylene (routed designs).

## SLIDES

Available in a range of sizes and the following materials:

1. Rota-moulded polyethylene (UV stabilised, Rating 8) with 930 density.
2. Stainless steel grades T304 & T316.
3. Galvanised steel side (HDG).
4. Fully reinforced, commercial grade aluminium (5005-H34). Minimum thickness 3mm.  
Powder-coated finish.

## ROPES

- Rope Diameter – 16mm and 18mm
- Rope Covering – Nylon
- Rope Core – Polypropylene
- Steel Reinforcement – 6 x galvanised wire strand 1570N/mm<sup>2</sup>
- Hydraulically pressed aluminium terminals
- Stainless steel hardware
- Plastic connectors – Nylon

## BOLTS

All bolts, fixtures and fittings meet Australian Standard AS 1112 and AS 1390

Pan head trilobular recess with cone point and tamper proof head.

- Case hardened to 450 HV5 minimum.
- Finish: zinc 5 micron and yellow dichromate.
- Size: M10 x 20 x 1.5 thread.

Also available as T302 stainless steel.



**FORPARK**  
A U S T R A L I A

## ROOFS

Available in the following materials:

1. Rota-moulded polyethylene (UV stabilised, rating 8) with 930 density.
2. Zincalume steel with powder-coat finish.

## TUNNELS

Available in the following materials:

1. Rota-moulded polyethylene (UV stabilised, rating 8) with 930 density.
2. Fully reinforced, commercial grade aluminium (5005-H34). Minimum thickness 3mm. Powder-coated finish.

## STEPS & STAIRS

Available in the following materials:

1. Aluminium (5005-H34) with powder coated finish.
2. Galvanised steel with powder coated finish.
3. Rota-moulded polyethylene (UV stabilised, rating 8) with 930 density.

## SPRING EQUIPMENT

Shapes available in the following materials:

Cast aluminium and fabricated steel.

2. Tri-laminate high density polyethylene.

Springs are rust protected. Fixing plates zinc passivated.

All aluminium, plates and springs have a powder-coated finish.

## TIMBER

Type: Meranti of the Shorea species - A light hardwood

Durable and resistant to insect attacks

Coated with a long lasting UV and weather resistant timber stain

All Forpark timber is responsibly sourced through a FSC certified supplier

## STANDARDS

Complies with relevant Australian Standards including: AS 4685:2014 (P1-6) | AS 4685.0:2017 | AS/NZS 4422:2016

\*All information is commercial in confidence and is the property of Forpark Australia. All information is correct as at February 2019.  
For details regarding Australian standards, warranties, insurances, QA and installation, please contact your local office



**FORPARK**  
A U S T R A L I A