

UPRIGHTS and SUPPORTS

Hot Dip Galvanised Steel - internally coated Grade: C450L0

Strength meets the strength requirements of Section 4.2.2 of AS 4685.1-2014.

Caps: Rolled and fabricated Aluminum or Moulded plastic (polyethylene).

POWDER COATING

All Aluminum components have a lead and TGIC free, baked polyester powder-coat finish.

Our finish of 80-120 microns greatly exceeds the required Australian Standard (AS3715-2002) of 60 microns.

PLATFORMS AND PLATFORM INFILL

1. Hot Dip Galvanised steel frame with 12mm reinforced rubber infills.
2. Fully reinforced, Marine Grade Aluminium (5005-H34). Minimum thickness 4mm, finished in textured powder-coat

STEEL PLAY COMPONENTS

1. Hot Dip Galvanised Steel - meeting the specifications C350L0.
 2. Stainless Steel – 316 Grade Stainless Steel.
- Finish: Hot Dip Galvanised steel and Electro Polished & Passivated Stainless Steel.

PLASTIC PLAY COMPONENTS

1. Rota-moulded - Polyethylene (UV stabilised, rating 8) with 930 density
2. Injection moulded – 30% Glass Filled Nylon

SLIDES

Available in a range of sizes and the following materials:

1. Rota-moulded polyethylene (UV stabilised, Rating 8) with 930 density.
2. Fully reinforced, commercial grade aluminum (5005-H34). Minimum thickness 3mm. Powder-coated finish.

ROOF

Stainless Steel 316 grade polished wire mesh, finished with powder coated edging

CHAINS

6mm short link stainless steel chain.

STANDARDS

Complies with relevant Australian Standards including: AS 4685:2014 (P1-6) | AS 4685.0:2017 | AS/NZS 4422:2016

*All information is commercial in confidence and is the property of Forpark Australia. All information is correct as at February 2019. For details regarding Australian standards, warranties, insurances, QA and installation, please contact your local office

PANELS

Available in the following materials:

1. Hot Dip Galvanised steel – minimum thickness 12mm.
2. Fully reinforced, Marine Grade Aluminum (5005-H34). Minimum thickness 6mm, finished with powder-coat.
3. Stainless steel 316 grade polished wire mesh, finished with powder coated edging.

ROPES

- Rope Diameter - 16mm
- Rope Covering - Nylon
- Rope Core - Polypropylene
- Steel Reinforcement - 6 x galvanised wire strand 1570N/mm²
- Hydraulically pressed aluminum terminals
- Stainless steel hardware
- Plastic connectors - Nylon

TUNNELS

Available in the following materials:

1. Rota-moulded polyethylene (UV stabilised, rating 8) with 930 density.
2. Fully reinforced, commercial grade aluminium (5005-H34). Minimum thickness 3mm. Powder-coated finish.
3. 12MM Reinforced rubber

BOLTS

T302 stainless steel - Size: M10 x 1.5 thread.

Galvanised steel - Size: M10 x 1.5 thread.

All bolts, fixtures and fittings meet Australian Standard AS 1112 and AS 1390.

TIMBER

Type: Meranti of the Shorea species - A light hardwood

Durable and resistant to insect attacks

Coated with a long lasting UV and weather resistant timber stain

All Forpark timber is responsibly sourced through a FSC certified supplier



WWW.FORPARKAUSTRALIA.COM.AU